

## Metadata during Key rollover

Here we try to describe how the Metadata looks after the different steps of Key rollover depending on what exists in the current XML file for the entity to start with. For explanation of the different steps see [Key rollover](#)

[illegible]

5	<pre> &lt;md:KeyDescriptor use=" encryption"&gt;   &lt;ds:KeyInfo&gt;     &lt;ds:X509Data&gt;       &lt;ds:X509Certificate&gt;New cert&lt;/ds:X509Certificate&gt;     &lt;/ds:X509Data&gt;   &lt;/ds:KeyInfo&gt; &lt;/md:KeyDescriptor&gt; </pre>	<pre> &lt;md:KeyDescriptor use="signing"&gt;   &lt;ds:KeyInfo&gt;     &lt;ds:X509Data&gt;       &lt;ds:X509Certificate&gt;New cert&lt;/ds:X509Certificate&gt;     &lt;/ds:X509Data&gt;   &lt;/ds:KeyInfo&gt; &lt;/md:KeyDescriptor&gt; </pre>	<pre> &lt;md:KeyDescriptor use=" encryption"&gt;   &lt;ds:KeyInfo&gt;     &lt;ds:X509Data&gt;       &lt;ds:X509Certificate&gt;New cert&lt;/ds:X509Certificate&gt;     &lt;/ds:X509Data&gt;   &lt;/ds:KeyInfo&gt; &lt;/md:KeyDescriptor&gt; &lt;md:KeyDescriptor use="signing"&gt;   &lt;ds:KeyInfo&gt;     &lt;ds:X509Data&gt;       &lt;ds:X509Certificate&gt;New cert&lt;/ds:X509Certificate&gt;     &lt;/ds:X509Data&gt;   &lt;/ds:KeyInfo&gt; &lt;/md:KeyDescriptor&gt; </pre>	<pre> &lt;md:KeyDescriptor&gt;   &lt;ds:KeyInfo&gt;     &lt;ds:X509Data&gt;       &lt;ds:X509Certificate&gt;New cert&lt;/ds:X509Certificate&gt;     &lt;/ds:X509Data&gt;   &lt;/ds:KeyInfo&gt; &lt;/md:KeyDescriptor&gt; </pre>
---	---	---	--	---